

HIKVISION®



KATALOG RETAIL 2024

www.hikvision.com



Produk NON-CCTV



NEW

DS-KV8113-WME1

- 2 MP camera with IR supplement
- One nametag button calling design for easier calls
- Built in card reader module
- Standard PoE power supply
- IK08 & IP65 higher protection level with aluminum alloy material
- Convenient Hik Connect APP mobile control



NEW

DS-KH6320-WTE1

- 7" Touch Screen Indoor Station,
- 7 inch Colorful TFT LCD, display resolution: 1024 * 600
- 10/100Mbps Ethernet, Wi Fi 802.11b/g/n
- standard PoE/ 12 VDC.
- TF card, max 32G
- 8 ch alarm input, 2xalarm output, 1x485



NEW

DS-KB8113-IM

- 2MP HD Camera with IR supplement providing excellent image quality
- Supports standard POE power supply
- Supports mechanical doorbell, easier to call
- Convenient Hik Connect APP Mobile Control: Receive calls, open the door and live view remotely
- Supports web configuration
- Higher protection level: IK09 & IP65



DS-KIS702Y

- IP video intercom kit for villa or house, only one call button.
- DS-KD8003-IME2/Surface x 1;
- DS-KH6320-WTE2 x 1;
- DS-KAD704 x 1;
- DS-KAW30-2N x 1;
- 16GB TF card x1;



DS-KIS202 (NEW)

- Analog Kit
- Kit including DS-KB2411-IM and DS-KH2220
- Include one monitor, one outdoor panel, 5-meter 4-wire cable, and other accessories
- you have to mark which standard adapter you want when you place an order



DS-KIS203(NEW)

- Water Proof Analog Kit
- Kit including DS-KB2421IM and DS-KH2220
- Include one monitor, one metal outdoor panel, 5-meter 4-wire cable, and other accessories
- you have to mark which standard adapter you want when you place an order



HOT

DS-KIS604-P

DS-KIS606-P

- IP video intercom kit for villa or house, only one call button.
- DS-KV8113-WME1 x1;
- DS-KH6320-WTE1 x1;
- 4 port standard PoE switch x1; (for KIS604-S)
- PSU x2;(for KIS604-P)
- 16GB TF card x1;
- No need additional power supply, but you have to mark which standard of power line type of the PoE switch you want when you place an order.(for KIS604-S)
- It includes 2 European power adapters, if you want to change the standard of power supply, you have to mark which standard of power adapter you want when you place an order.(for KIS604-P)

DS-K1T8003MF

- Terminal akses kontrol sidik jari
Layar LCD 2,4 inci dibekali dengan modul pembaca kartu Mifare, Komunikasi:TCP/IP, Ehome
- Kapasitas 1000 pengguna, 1000 sidik jari, 1000 kartu Mifare dan Maks. 100.000 catatan kejadian;
- Mendukung Kontrol Akses dan Fungsi Absensi, modul optic sidik jari;
- Mendukung 6 status kehadiran, termasuk jam masuk, jam pulang, istirahat dimulai, istirahat selesai, lembur di mulai, lembur selesai
- Membuka pintu dari jarak jauh melalui klien seluler Hik-Connect, tamper alarm.



DS-K1T801M

- Standalone Access Control Terminal, Built-in Mifare card reading module,
- Storage with 3,000 cards; 12 Keys keyboard and doorbell, DC 12V/1A



NEW

DS-K1T804AMF (NEW)

DS-K1T804AEF

- 2.4 inch LCD Display Standalone Access Control Terminal, Built-in Mifare card (M) or EM card (E) reading module,
- Storage with 3,000 cards, 3,000 fingerprints and 100,000 access control events;
- Support Access Control and Time Attendance Function, Optical Fingerprint Module;
- Uplink Communication: TCP-IP, WIFI; Supports Wiegand, Supports ISUP5.0, ISAPI
- Multiple languages: English, Spanish, Italian, French, Portuguese (Brazilian), Vietnamese, Arabic, Thai, Turkish, Indonesian, Ukrainian



NEW

DS-K1A8503MF

DS-K1A8503EF

DS-K1T805MBFWX

- 2.4 inch LCD Display Standalone Access Control Terminal, Built-in Mifare card (M) or EM card (E) reading module,
- Storage with 3,000 cards, 3,000 fingerprints and 100,000 access control events;
- Support Access Control and Time Attendance Function, Optical Fingerprint Module;
- Uplink Communication: TCP-IP, WIFI; Supports Wiegand, Supports ISUP5.0, ISAPI
- Multiple languages: English, Spanish, Italian, French, Portuguese (Brazilian), Vietnamese, Arabic, Thai, Turkish, Indonesian, Ukrainian

AKSES KONTROL TANPA SENTUH

MinMoe DS-K1T321 Series

DS-K1T321MFX
DS-K1T321EFX
DS-K1T321MFWX

- 2,4 inch LCD screen, 2 MP lens
- Multiple authentication methods, including face, fingerprint, card (M1 card), and PIN, etc.
- Max. 500 faces, 3000 cards, 3000 fingerprints and 150,000 events
- Face recognition duration < 0.2 s/User
- Supports ISAPI and ISUP 5.0 protocols
- Configuration via the PC web client and mobile web client
- Supports wired network and Wi Fi (APmode)
- Supports wiring with secure door control unit or card reader via RS 485

500
Faces

3,000
Fingerprints
(optional)

3,000
Cards



DS-K1T343MFX

DS-K1T343MX

DS-K1A340

- Face Recognition Terminal (A : Time Attendance only) , 4.3-inch LCD touch screen, 2 Mega pixel wide-angle lens, Built-in Mifare card reading module (M);
- Max.1,500 faces capacity Max.3,000 cards (M); Max.3,000 fingerprints capacity (F), up to 300,000 attendance records
- Face recognition in dark environment, IP65,
- Two-way audio with client software, indoor station, and master station
- Supports TCP/IP (Only T Model), DC 12V/1A, Supports ISUP5.0, ISAPI
- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- (A) Support Local Attendance
- multiple languages: English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)
- Configuration via the web client
- Face Recognition Accuracy Rate > 99%, Duration(1:N) ≤0.2s, Distance: 0.3m ~ 1.5m



DS-K1T342MX

DS-K1T342MFX

DS-K1T342MFWX

- Face Recognition Terminal, 4.3-inch LCD touch screen, 2 Mega pixel wide-angle lens, Built-in Mifare card reading module;
- Max.1,500 faces capacity Max.3,000 cards; Max.3,000 fingerprints capacity (F)
- Face recognition in dark environment, IP65, Configuration via the web client
- Two-way audio with client software, indoor station, and master station
- Supports TCP/IP, WiFi, DC 12V/1A, Supports ISUP5.0, ISAPI
- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- multiple languages: English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)
- Face Recognition Accuracy Rate > 99%, Duration(1:N) ≤0.2s, Distance: 0.3m ~ 1.5m



NEW

DS-K1T341CMF

DS-K1T341CM

- Face Recognition Terminal, 4.3-inch LCD touch screen, 2 Mega pixel wide-angle lens, Built-in Mifare card reading module;
- Max.1,500 faces capacity Max.3,000 cards; Max.3,000 fingerprints capacity (F)
- Face recognition in dark environment, IP65, Configuration via the web client
- Two-way audio with client software, indoor station, and master station
- Supports TCP/IP, WiFi, DC 12V/1A, Supports ISUP5.0, ISAPI
- Supports 6 attendance status, including check in, check out, break in, break out, overtime in, overtime out
- multiple languages: English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)
- Face Recognition Accuracy Rate > 99%, Duration(1:N) ≤0.2s, Distance: 0.3m ~ 1.5m

Kecepatan Koneksi Lancar di Setiap Kesempatan



*free exchange



NEW

DS-3WR12GC

- Four 5 dBi amplified antennas
- Beamforming optimizes signal
- Beamforming optimizes signal
- Dual band Smart signal switching
- Dual band Smart signal switching
- Broadband account synchronization



NEW

DS-3WR4G12C

- AC1200 Dual band Wi Fi
- 4G Boost Faster Speed
- Instantly Access a Mobile Network With a SIM Card



DS-3WR3N

- 5-dBi amplified antennas
- Dual antennas for maximum coverage
- Supports IPTV
- Data Rate: 2.4 GHz: 300 Mbps
- Antenna: Two 5-dBi amplified antennas
- Wireless Standard: IEEE 802.11b/g/n @ 2.4 GHz
- Working Frequency Band: 2.4 GHz



DS-3WR12C

- Four 5-dBi amplified antennas
- Beamforming optimizes signal
- Dual band – Smart signal switching
- Broadband account synchronization
- Data Rate: 5 GHz: 867 Mbps; 2.4 GHz: 300 Mbps
- Antenna: Four 5-dBi amplified antennas
- Wireless Standard: IEEE 802.11/a/n/ac wave 2 @ 5 GHz; IEEE 802.11b/g/n @ 2.4 GHz
- Working Frequency Band: 2.4 GHz, 5 GHz

Hikvision Kabel Jaringan

Pilihan Pertama, Selamanya Terpercaya

Pilihan untuk

Sistem CCTV

Lapisan tahan Api



Bahan tahan terhadap api peregangan, dan penuaan

Teknologi Memutar yang tepat



Peningkatan kemudahan aliran ke data transmisi

99,95%
Kemurnian Cu



Konduktivitas yang lebih tinggi dengan redaman transmisi sinyal yang lebih rendah

0.565 mm
Diameter Kawat

Transmisi sekarang lebih stabil dengan resistensi yang berkurang



NEW

DS-1LN6UZCO

- CAT6 U/UTP Network
- Cable (Solid Copper,0.5mm)



NEW

DS-1LN6UECO

- CAT6 U/UTP Network
- Cable (Solid Copper,0.53mm)



NEW

DS-1LN6UU/CCA

- CAT6 U/UTP Network
- Cable (Solid Copper,0.57 mm)



DS-1LN6-UE-W

- UTP CAT 6, 305 meters, Core diameter: 0.53mm, Solid Copper, CM, white



DS-1LN5E-E/E

- UTP CAT 5E, 305 meters,
- Core diameter: 0.45mm
- OFC, CMX, gray



DS-1LN6U-G

DS-1LN6U-W/CCA

- UTP CAT 6, 305 meters
- Core diameter: 0.585mm, CCA, white
- Core diameter: 0.55mm Solid Copper, gray

HIKVISION®

KATALOG RETAIL 2024